



Polaris



170
Stella



180
Splendour



300
Solar



350
Starlight



500
Radiance



520
Glimmer



540
Cosmic



545
**Coastal
Blackbutt**



555
**Old Spotted
Gum**



560
Astro



720
Galaxy



750
Moonstone

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. Please note some colours in this range (as noted above and on front of samples) have a visual design effect that results in tonal variations amid the boards for a natural timber look. Please seek to view larger samples and consult with your retailer for further advice. *Subject to proper installation and maintenance.

Polaris

The versatile vinyl plank range Polaris takes the look, feel and design of natural timber floors and adds a few extra touches. It is durable, easy to maintain and waterproof*. The exquisite colour range provides endless options for a variety of interiors for a traditional look without the maintenance.

Technical Data

Type	Vinyl Plank	M² per Box	3.62m ²
Plank Thickness	3mm	M² per Pallet	202.72m ²
Wear Layer	0.3mm	Finish	Matte
Dimensions	1219mm (L) x 228mm (W)	Surface	Woodgrain - Semi Wild
Planks per Box	13	Profile	Square Edge
Colours	12	Protective Coating	PU Coating
Installation Method	Direct Stick		

Performance

Classification	23, 33	ISO 10582
Dimensional Stability	≤ 0.25%	EN 434
Abrasion Rating	Group P	EN 660-1
Residual Indentation	< 0.1mm	EN 433
Furniture Leg	No Damage	EN 424
Castor Chair	No Damage	EN 425
Curly Resistance to Heat	≤ 2mm	EN 434
Thermal Performance	0.07m ² K/W Suitable - max. 27°C	EN 12667
Impact Sound Reduction	Ln,W 60 IIC 50	ISO 10140-3 ASTM E492-09
Light Fastness	≥ 6	EN ISO 105-B02
Chemical Resistance	Good Resistance	EN 423
Electrical Propensity	Pass	EN 1815
Fire Classification	CRF 10.4kW/m ² Smoke Value 83% Minutes	AS/ISO 9239
Slip Resistance	R10	AS/NZ 4586-2013
Suitable for wet areas	Yes - subject to proper installation and maintenance	
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide www.godfreyhirst.com	

Sustainability

VOC Rating	Available on Request
-------------------	----------------------

