

## PRODUCT

## Swatches



100  
STIRLING

**Timber**  
Standard Board  
1820mm x 190mm



530  
DOVER

**Timber**  
Standard Board  
1820mm x 190mm



560  
ASTOR

**Timber**  
Standard Board  
1820mm x 190mm



580  
WINDSOR

**Timber**  
Standard Board  
1820mm x 190mm



700  
LINCOLN

**Timber**  
Standard Board  
1820mm x 190mm



710  
HELMSLEY

**Timber**  
Standard Board  
1820mm x 190mm



300  
HAMPTON

**Timber**  
Wide Board  
2130mm x 240mm



500  
YORK

**Timber**  
Wide Board  
2130mm x 240mm



520  
CARLISLE

**Timber**  
Wide Board  
2130mm x 240mm



540  
BERKSHIRE

**Timber**  
Wide Board  
2130mm x 240mm



720  
ROCHESTER

**Timber**  
Wide Board  
2130mm x 240mm



780  
SCARBOROUGH

**Timber**  
Wide Board  
2130mm x 240mm



## REGAL OAK

Regal Oak Handcrafted Timber has a distressed ultra matte finish and round edges for a rustic style. Wide boards are also available in selected hues. The stunning colours are smoked rather than stained to provide consistent colour all the way through the hardwood timber surface. This distressed style is ideal for helping to conceal everyday wear.

## PRODUCT

## Specifications

## REGAL OAK - Timber Product Details

## Technical Data

Type	Engineered Timber
Plank Thickness	14mm
Wear Layer	3.2mm
Dimensions	1820mm x 190mm (Standard) 2130mm x 240mm (Wide)
Planks per Box	6 boards. Nested/Random lengths will occur, gap up to 18%
M <sup>2</sup> per Box	2.075m <sup>2</sup> (Standard) 3.067m <sup>2</sup> (Wide)
M <sup>2</sup> per Pallet	114.125m <sup>2</sup> (Standard) 101.211m <sup>2</sup> (Wide)
Colours	12 (6 Standard / 6 Wide)
Finish	Matte
Surface	Distressed
Profile	Round Edge
Substrate Layer	Hevea Core
Backing Layer	Spruce
Installation Method	5G Insta Clic. Please refer Installation Instructions for further details

## Performance

Coating System	UV Coating Wearguard™ 7 Coat System (UV Coating)	
Abrasion Rating	6 coats > = 5000 revolutions	ASTM D 4060-CS 17
Moisture Content	7% (+/- 2%) at time of delivery	EN 13183-1
Reaction to Fire	CRF 3.1kW/m <sup>2</sup> Smoke Value 9% Minutes (Over Underlay)	AS/ISO 9239
Slip Resistance	R10 / P4	AS4586:2013
Warranty†	Consumer Guarantee	
Recommended Adhesive	Refer Godfrey Hirst Adhesive Recommendations	

## Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Timber products must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Floors Timber Installation Instructions.

†Warranty terms and conditions apply.

Test results and certificates are available on request.