



Villa



100
White Sands



500
Alpine Oak




510
Summer Blonde



520
Autumn Amber



535
Wild Fawn



540
Raffia



550
Havana



780
Silver Finch



770
Truffle



790
Espresso

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. *Subject to proper installation and maintenance.

Villa

Villa highlights the authentic texture and grain of timber. Your floor becomes the focal point of your interior, with the unique pattern features of each board accentuated by subtle micro bevelled edges. Transform your space today with this stunning, high quality oak floor. Characterised by delicate impressions of organic construction, this collection will create a casual authentic ambience for your personal retreat. One colour is also available with extreme matte oil for a stunning modern finish.

Technical Data

Type	Engineered Timber	Grading	Select ABC
Board Thickness	14mm	Colours	10
Wear Layer	3.2mm	Finish	Matte
Dimensions	1820mm (L) x 190mm (W)	Surface	Stain (9 colours Robust Lacquer, 1 colour Extreme Matt Oil)
Boards per Box	6 boards (Nested / Random lengths will occur. Up to 16%)	Substrate Layer	Hevea Core
M² per Box	2.075m ²	Core & Backing Layer	Spruce
M² per Pallet	114.125m ²	Profile	Micro Bevel Edge
Installation Method	5G Insta Clic [®]		

Performance

Coating System	Wearguard™ 7 Coat System (UV Coating)	
Abrasion Rating	7 coats > = 6000 revolution	ASTM D 4060-CS 17
Impact Sound Reduction	ΔLw = 17dB IIC 53	ISO 10140-3 ASTM E492-09
Moisture Content	7% (+/- 2%) at time of delivery	EN 13183-1
Reaction to Fire	CRF - 3.1 kW/m ² (Over Underlay)	AS/ISO 9239
Slip Resistance	R10 / P3	AS/NZ 4586 - 2013
Warranty†	Consumer Guarantee	
Recommended Adhesive	Refer Godfrey Hirst Adhesive Recommendation Guide	

Sustainability

VOC Rating	CTEC Compliant for VOC Emission Rate Limits
Indoor Air Quality	Green Building Council compliant for VOC emission rate limits



All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Timber products must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Floors Timber Installation Instructions.

†Warranty terms and conditions apply. Test results and certificates are available on request.

^Nested/Random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.